

GIORGIO GRAESAN and Friends	TECHNICAL SHEET SPATULA STUHHI Due Mani	Code	TDS1001_DUE_00
		Revision	00
		Date	29/10/2025

1. DESCRIPTION

SPATULA STUHHI is a high-quality, long-aged, natural lime putty-based glossy stucco. Marble powders and specific additives give the product excellent adhesion to the substrate and excellent flow upon application, achieving a quick finish. This innovative product, born from the Venetian tradition of glossy stucco, has been modified and adapted to meet current needs for color and quick application. SPATULA STUHHI allows for maximum breathability and is an excellent anti-mold and anti-bacterial agent due to its alkaline nature.

SPATULA STUHHI is an ecological coating and does not contain solvents.

2. USE

SPATULA STUHHI is recommended for decorating interior spaces. It can be applied using two different techniques:

- CLASSIC with crossed spatula movements;
- HIGH LIGHT with vertical spatula movements.

For further details on how to apply it, please refer to the videos published on our website.

3. SUBSTRATE PREPARATION

A correct preparation of the substrate is indispensable for the finish to show its qualities to the fullest.

The substrate must be dry and free from any irregularities or cracks.

It is important to carry out the elimination of any poorly-anchored or powdery paint or plaster, being sure to wash or remove any mould or dust that may be present. Before applying PRIMUS SABBIA, the surface must always be well bonded. If not, apply an insulating primer, which is especially recommended for plasterboard or stucco walls or analogous products.

In the case of application on tiles, smooth the surface with PRIMUS AGGRAPPANTE.

4. APPLICATION METHOD

SPATULA STUHHI Any water on the surface should be regarded as normal and should be removed prior to use. To color, before adding the chosen COLORING ADDITIVE, reduce the viscosity of the product by mixing it with a drill and a special MIX stirrer. Then add the COLORING ADDITIVE in the quantity indicated in the catalog and mix until the color is completely homogenized. Before applying, let the colored product rest for at least 12 hours. For more intense colors, we recommend adding the THICKENING ADDITIVE immediately after mixing the color additive, then let it rest for at least 12 hours. The product is applied with the KIT/NUDO trowel.

First coat: It should be applied taking care to spread it evenly.

Second coat: proceed when the first coat is dry (after at least 12 hours), taking care to spread it evenly creating a flat surface free of depressions, at this point continue with the enrichment of the product, wet on wet, then proceed with the final polishing.

To achieve a uniform color result, we recommend using material colored with only a single batch of coloring additive. The shine is achieved by the pressure between the steel trowel blade and the coating surface. For this reason, we recommend using a trowel with a perfectly intact blade edge and free of irregularities.

GIORGIO GRAESAN and Friends	TECHNICAL SHEET SPATULA STUHHI Due Mani	Code	TDS1001_DUE_00
		Revision	00
		Date	29/10/2025

5. TOOL CLEANING

Cleaning of the tools should be done immediately after use with water.

6. PROTECTING AND CLEANING

Depending on the level of protection and final shine you want to achieve SPATULA STUHHI can be protected with CERA DEL VECCHIO or CERA D'API. The surface is thus breathable and washable, but not completely water-repellent. If treated with CERA DEL VECCHIO or CERA D'API, it can be washed using LATTE DETERGENTE (diluted 50 ml in 1 litre of water).

7. SAFETY RECOMMENDATIONS AND RISK IDENTIFICATION

Causes severe eye injuries. Causes skin irritation.

Use the product according to current hygiene and safety regulations. After use do not disperse the containers in the environment. Allow the residues to dry well and treat them as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show the healthcare operator the container or label. Do not dispose of residue in sewers, waterways and soil.

For further information, see the safety data sheet available on the website: www.giorgiograesan.it

TECHNICAL SPECIFICATIONS: APPLICATION	
Dilution	Product ready for use
Mixing	Always mix before use and let it rest for 12 hours
Colouring	169 colours in the catalogue (before use, eliminate any skin and mix)
Tools	Steel trowel KIT/NUDO
Primer	PRIMUS NATURALE
Conditions of application	From +10°C to +30°C with relative humidity <85%
Number of coats	2
Drying time	Each coat dries in 12 hours at 20°C
Curing time	48 hours at 20°C
Stable carbonatation	28 days
Protective coating	CERA DEL VECCHIO, CERA D'API
Washability	If protected with CERA DEL VECCHIO or CERA D'API

TECHNICAL SPECIFICATIONS: CONSUMPTION	
PRIMUS NATURALE	6 – 7 m ² /litre
SPATULA STUHHI (2 coats)	1 kg/m ²
CERA DEL VECCHIO or CERA D'API	20 – 30 gr/m ²

TECHNICAL SPECIFICATIONS: COLOURING				
COLOUR	24 KG	8 KG	4 KG	2 KG
S1	3x750 ml	750 ml	375 ml	3x62 ml
S2	750 ml	250 ml	125 ml	62 ml
S3	3x62 ml	62 ml	31 ml	15.5 ml
S4	62 ml	20 ml	10 ml	5 ml

GIORGIO GRAESAN and Friends	TECHNICAL SHEET SPATULA STUHHI Due Mani	Code	TDS1001_DUE_00
		Revision	00
		Date	29/10/2025

TECHNICAL SPECIFICATIONS: PRODUCT	
Composition	PIT LIME seasoned for at least 6 months, finely filtered and powdered marble
Specific weight	1.56 ± 0.03 Kg/litre
pH	12.5
EU limit value (Dir. 2004/42/EC) Cat. A/l: paints for decorative effects (water-based): 200 g/l	Maximum VOC content of base product: 0 g/l Maximum VOC content of colored product: 20 g/l
Storage conditions	Store in a tightly closed paint bucket, even after use and after having cleaned the sides and lid of the bucket, keep in a cool and dry place within the temperature range of +5°C and +30°C
Packaging	2 – 4 – 8 – 24 kg

Giorgio Graesan & Friends guarantees that the information on this datasheet is provided to the best of its experience and technical and scientific knowledge, however it cannot assume any responsibility for the results obtained with its use as the conditions of application are beyond its control. It is advisable to always check the actual suitability of the product for the specific case. This document cancels and replaces each previous datasheet.

For further technical information contact **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.