

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDS1018_01
	FRAMMENTI ARGENTO	Revision	01
		Date	29/01/2019

1. DESCRIPTION

FRAMMENTI ARGENTO is a transparent, glossy, water-based protective finish enriched with silver fragments. It waterproofs finishes, significantly increasing washability and resistance to stains and dirt in general.

2. USE

Suitable for application on internal walls of bathrooms, kitchens or other situations that require protection from water even in case of direct contact.

FRAMMENTI ARGENTO, once dry, revives surfaces, giving them a shiny appearance and a typical wet effect.

3. PREPARING THE SUBSTRATE

The surface on which it is to be applied must be clean, dry, adherent.

4. METHOD OF APPLICATION

FRAMMENTI ARGENTO is ready for use, only dilute when required.

The substrate must be **completely dry**, wait at least 24 hours after applying the product to be protected.

Product to be protected	Single coat
FILI DI SETA – MINIMAL	FRAMMENTI ARGENTO undiluted and applied with roller PE 13
GIOIA – WHITE – ORO	FRAMMENTI ARGENTO undiluted and applied with roller PE 13
NEVE – VIA LATTEA	FRAMMENTI ARGENTO undiluted and applied with roller PE 13
CASA DEI SOGNI	FRAMMENTI ARGENTO undiluted and applied with roller PE 13
MINIMAL	FRAMMENTI ARGENTO undiluted and applied with roller PE 13
CREA IL TUO UNIVERSO	FRAMMENTI ARGENTO undiluted and applied with roller PE 13

As water-based protective, if applied on a still wet surface it tends to whiten and its protective effect is reduced.

Apply as much of the product as possible and remove the excess. We recommend applying the product gently without vigorously rubbing.

If a milky appearance and brush strokes appear during application, these will disappear with the drying process.

On corners or other spots hard to reach, apply with a brush, especially along joints between different surfaces.

Wait 12 hours between coats. For better protection, we recommend to apply the product in several coats.

Once done, seal the edges in contact with other surfaces (shower trays, taps, kitchen countertops) with suitable silicone, to avoid water stagnating, which would result in the formation of haloes or crazing.

5. CLEANING THE TOOLS

Clean the tools with water immediately after use.

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDS1018_01
	FRAMMENTI ARGENTO	Revision	01
		Date	29/01/2019

6. CLEANING THE FINISHED PRODUCT

Clean with LATTE DETERGENTE (dilute 50 ml in 1 litre of water).

7. SAFETY RECOMMENDATIONS AND RISK IDENTIFICATION

The product does not require labelling according to current regulations. Use the product according to current health and safety regulations; after use, do not dispose of containers to the environment; let residue dry thoroughly and handle as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. Do not empty into drains, waterways or soil.

For more information, see safety data sheet available on: www.giorgiograesan.it

TECHNICAL CHARACTERISTICS: APPLICATION	
Dilution	Product is ready for use; may be diluted as needed
Mixing	Always mix before use
Colouring	Not provided
Tools	Roller PE13
Primer	Not provided
Conditions of application	From +10°C to +30°C with relative humidity < 85%
Number of coats	1 or 2, depending on the substrate to protect
Drying time	Each coat dries in 4 – 6 hours at 20°C
Wait time for 2 nd coat	12 hours at 20°C
Curing time	24 hours at 20°C
Washability	Full wash with LATTE DETERGENTE

TECHNICAL CHARACTERISTICS: COVERAGE	
FRAMMENTI ARGENTO	7 – 8 m ² /litre

TECHNICAL CHARACTERISTICS: PRODUCT	
Composition	Acrylic copolymer in aqueous emulsion
Specific weight	1.05 ± 0.03 Kg/litre
pH	>8.0 – 8.5 after 30 days
EU limit value (Directive 2004/42/EC) Cat. A/l: decorative effect coatings (water-borne): 200 g/l	Maximum VOC content 13,17 g/l
Storage conditions	Keep in tightly sealed container, even after use and after cleaning the sides and lid of the tin, in a cool, dry place at temperatures between +5°C and +30°C
Packaging	1 – 2,5 litres

Giorgio Graesan & Friends guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge, however cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. We recommend always checking the actual suitability of the product for each specific case. This sheet nullifies and replaces any previous version.

For more information, call phone number **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.