

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDS1019_03
	VETRO LUCIDO	Revision	03
		Date	29/10/2025

1. DESCRIPTION

VETRO LUCIDO is a protective, clear, glossy, water-based finish with acrylic polymers. Makes finishes waterproof, considerably increasing washability and resistance to stains and dirt.

2. USE

Suitable for application on the interior walls of bathrooms, kitchens or other settings that require protection from water. Ideal for interiors of shower stalls or other settings in direct contact with water. VETRO LUCIDO, once dry, revitalises surfaces, giving a shiny appearance and a classic wet-look effect.

3. PREPARING THE SUBSTRATE

The surface on which it is to be applied must be clean, dry, adherent.

4. METHOD OF APPLICATION

VETRO LUCIDO is ready for use, only dilute when required.

The substrate must be **completely dry**, wait at least 24 hours after applying the product to be protected, if applied on a still wet surface it tends to whiten and its protective effect is reduced.

Product to be protected	First coat	Second coat
ISTINTO PIETRA SPACCATA ISTINTO PIETRA ZEN ISTINTO CEMENTO NATURALE ISTINTO PIETRA INTAGLIATA	ISTINTO NATURALE VETRO SATINATO undiluted and applied with PE 10 brush until wall refuses it	VETRO LUCIDO undiluted and applied with PE 3 brush
	ISTINTO COLORATO with GIOIA - WHITE - ORO VETRO LUCIDO undiluted and applied with PE 3 brush	Just to give more protection
ISTINTO PIETRA LEVIGATA ISTINTO PIETRA CONTEMPORANEA ISTINTO ESTASI DI MARMO	VETRO SATINATO undiluted and applied with PE 13 roller until wall refuses it	VETRO LUCIDO undiluted and applied with PE 13 roller
MURO NATURALE – SPATULA STUHHI SPIRITO LIBERO	VETRO SATINATO undiluted and applied with PE 13 roller until wall refuses it	VETRO LUCIDO undiluted and applied with PE 13 roller
FILI DI SETA – MINIMAL	VETRO LUCIDO undiluted and applied with PE 13 roller	Just to give more protection
GIOIA – WHITE – ORO - CASA DEI SOGNI	VETRO LUCIDO undiluted and applied with PE 13 roller	Just to give more protection
SARTI IN PARETE	VETRO LUCIDO undiluted and applied with PE 13 roller	VETRO LUCIDO undiluted and applied with PE 13 roller

Apply as much of the product as possible and remove the excess. We recommend applying the product gently without vigorously rubbing. If a milky appearance and sponge or brush strokes appear during application, these will disappear with the drying process. On corners or other spots hard to reach, apply with a brush, especially along joints between different surfaces.

Wait 12 hours between coats.

For better protection, especially inside shower enclosures and behind kitchen tops, we recommend applying at least two coats of VETRO SATINATO undiluted until wall refuses it, then apply a coat of VETRO LUCIDO.

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDS1019_03
	VETRO LUCIDO	Revision	03
		Date	29/10/2025

Once done, seal the edges in contact with other surfaces (shower trays, taps, kitchen countertops) with suitable silicone, to avoid water stagnating, which would result in the formation of haloes or crazing.

5. CLEANING THE TOOLS

Clean VETRO LUCIDO off tools by rinsing with water.

6. CLEANING THE FINISHED PRODUCT

Clean with LATTE DETERGENTE (50 ml LATTE DETERGENTE in 1 litre of water).

7. SAFETY RECOMMENDATIONS AND RISK IDENTIFICATION

The product does not require labelling according to current regulations. Use and store according to current health and safety regulations; after use, do not dispose of containers to the environment; let residue dry thoroughly and handle as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. Do not empty into drains, waterways or soil.

For more information, see safety data sheet available on: www.giorgiograesan.it

TECHNICAL CHARACTERISTICS: APPLICATION	
Dilution	Product is ready for use; may be diluted as needed
Mixing	Always mix before use
Colouring	Not provided
Tools	PE 3 brush or PE 10 brush or PE 13 roller
Primer	Not provided
Conditions of application	Da +10°C a +35°C con umidità relativa < 85%
Number of coats	From +10°C to +35°C with relative humidity < 85%
Drying time	1 or 2, depending on the substrate to protect
Wait time for 2 nd coat	Each coat dries in 4 – 6 hours at 20°C
Curing time	12 hours at 20°C
Washability	24 hours at 20°C

TECHNICAL CHARACTERISTICS: COVERAGE	
VETRO LUCIDO	7 – 8 m ² /litres

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDS1019_03
	VETRO LUCIDO	Revision	03
		Date	29/10/2025

TECHNICAL CHARACTERISTICS: PRODUCT	
Composition	Acrylic copolymer in water emulsion
Specific weight	1.05 ± 0.03 kg/litre
pH	>8.0 – 8.5 after 30 days
EU limit value (Directive 2004/42/EC) Cat. A/l: decorative effect coatings (water-borne): 200 g/l	Maximum VOC content 13.17 g/l
Storage conditions	Keep in tightly sealed container, even after use and after cleaning the sides and lid of the tin, in a cool, dry place at temperatures between +5°C and +30°C
Packaging	1 – 2.5 litres

Giorgio Graesan & Friends guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge, however cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. We recommend always checking the actual suitability of the product for each specific case. This sheet nullifies and replaces any previous version.

For more information, call phone number **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.