

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDS1027_01
	VETRO SATINATO	Revision	01
		Date	29/10/2025

1. DESCRIPTION

VETRO SATINATO is a protective finish composed of water-based acrylic polymers, with a transparent and satin finish. Specifically, it waterproofs lime-based finishes, significantly increasing washability and resistance to stains and dirt. The surface becomes soft and silky to the touch.

2. USE

Also suitable for application on interior walls of bathrooms, kitchens, or other areas requiring water protection. Suitable for shower enclosure interiors or other areas in direct contact with water. VETRO SATINATO, once dry gives the surface a natural and satin look. Also indicated as an insulating primer before applying IPER VETRO on surfaces made with our lime-based products.

3. PREPARING THE SUBSTRATE

The surface on which it is to be applied must be clean, dry, adherent.

4. METHOD OF APPLICATION

VETRO SATINATO is ready for use.

The support must be **completely dry**, wait until the surface is completely dry, at least 12-24 hours, depending on the type of product to be protected, if applied on a still wet surface it tends to whiten and its protective effect is reduced.

Product to be protected	First coat	Second coat
ISTINTO PIETRA SPACCATA ISTINTO PIETRA ZEN	ISTINTO NATURALE VETRO SATINATO undiluted applied with PE 10 brush	VETRO SATINATO undiluted applied with PE 3 brush
ISTINTO CEMENTO NATURALE ISTINTO PIETRA INTAGLIATA	ISTINTO COLORATO with GIOIA - WHITE - ORO VETRO SATINATO undiluted applied with PE 3 brush	Only to give more protection
ISTINTO PIETRA LEVIGATA ISTINTO PIETRA CONTEMPORANEA ISTINTO ESTASI DI MARMO	VETRO SATINATO undiluted and applied with PE 13 roller until wall refuses it	VETRO SATINATO undiluted and applied with PE 13 roller
MURO NATURALE – SPATULA STUHHI SPIRITO LIBERO	VETRO SATINATO undiluted applied with PE 13 roller until wall refuses it	VETRO SATINATO undiluted and applied with PE 13 roller
FILI DI SETA – MINIMAL	VETRO SATINATO undiluted applied with PE 13 roller	Only to give more protection
GIOIA – WHITE – ORO	VETRO SATINATO undiluted applied with PE 13 roller	Only to give more protection
CASA DEI SOGNI	VETRO SATINATO undiluted applied with PE 13 roller	Only to give more protection

Apply carefully, avoiding streaks. After 4-6 hours, apply the second coat in homogeneous and evenly way. On smooth surfaces, a PE13 roller can be used in both coats to avoid bristle marks. Any milky appearance and brush marks that may appear during application will disappear once dry..

In corners or other hard-to-reach places, go over them with a brush, especially at the points where the various surfaces meet.

Once done, seal the edges in contact with other surfaces (shower trays, taps, kitchen countertops) with suitable silicone, to avoid water stagnating, which would result in the formation of haloes or crazing.

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDS1027_01
	VETRO SATINATO	Revision	01
		Date	29/10/2025

5. CLEANING THE TOOLS

Clean VETRO SATINATO off tools by rinsing with water.

6. CLEANING THE FINISHED PRODUCT

Clean with LATTE DETERGENTE (50 ml LATTE DETERGENTE in 1 litre of water).

7. SAFETY RECOMMENDATIONS AND RISK IDENTIFICATION

The product does not require labelling according to current regulations. Use and store according to current health and safety regulations; after use, do not dispose of containers to the environment; let residue dry thoroughly and handle as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show his container or label. Do not empty into drains, waterways or soil.

For more information, see safety data sheet available on: www.giorgiograesan.it

TECHNICAL CHARACTERISTICS: APPLICATION	
Dilution	Product is ready for use
Mixing	Always mix before use
Colouring	Not provided
Tools	PE3 or PE10 Brush - PE13 Roller
Primer	Not provided
Conditions of application	From +10°C to +30°C with relative humidity < 85%
Number of coats	2
Drying time	Each coat dries in 4 – 6 hours at 20°C
Wait time for 2 nd coat	12 hours at 20°C
Curing time	24 ore a 20°C
Washability	Full wash with LATTE DETERGENTE

TECHNICAL CHARACTERISTICS: COVERAGE	
VETRO SATINATO	13 m ² /litre for two coats

TECHNICAL CHARACTERISTICS: PRODUCT	
Composition	Acrylic copolymer in aqueous emulsion
Specific weight	1.01 ± 0.03 Kg/litre
pH	9.2
EU limit value (Directive 2004/42/EC) Cat. A/l: decorative effect coatings (water-borne): 200 g/l	Maximum VOC content 13.92 g/l
Storage conditions	Keep in tightly sealed container, even after use and after cleaning the sides and lid of the tin, in a cool, dry place at temperatures between +5°C and +30°C
Packaging	1 – 2,5 litres

Giorgio Graesan & Friends guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge, however cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. We recommend always checking the actual suitability of the product for each specific case. This sheet nullifies and replaces any previous version.

For more information, call phone number **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.