

<b>GIORGIO GRAESAN</b> and Friends	TECHNICAL SHEET  <b>PRIMUS AGGRAPPANTE</b>	Code	TDS1035_00
		Revision	00
		Date	22/08/2022

## 1. DESCRIPTION

PRIMUS AGRAPPANTE is a single-component, ready-to-use acrylic resin-based smoothing filler. Formulated with natural aggregates of calibrated grain size, neutral in color, and solvent-free.

## 2. USE

Featuring high adhesion, particularly suitable for smoothing old tile coverings and as a base for the subsequent application of lime or acrylic-based products.

## 3. PREPARING THE SUBSTRATE

Correct preparation and cleaning of the substrate is essential for a perfect coating result. Furthermore, the substrate must be dry, free from dust and well consolidated.

## 4. METHOD OF APPLICATION

When applying to tiles, after degreasing the wall with denatured ethyl alcohol, level any wide joints with a first spot coat of PRIMUS AGGRAPPANTE. Let it dry, then apply a uniform and smooth coat of PRIMUS AGGRAPPANTE using a KIT/I stainless steel trowel.

If you want a completely smooth surface, once the substrate is dry, we recommend applying a suitable leveling filler and an insulating primer.

Let it dry for at least 24 hours before applying the chosen decorative coating.

## 5. CLEANING THE TOOLS

Clean the tools with water immediately after use.

## 6. PROTECTING AND CLEANING

Not expected, it is a primer.

## 7. SAFETY RECOMMENDATIONS AND RISK IDENTIFICATION

The product does not require labelling according to current regulations. Use the product according to current health and safety regulations; after use, do not dispose of containers to the environment; let residue dry thoroughly and handle as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. Do not empty into drains, waterways or soil.

For more information, see safety data sheet available on: [www.giorgiograesan.it](http://www.giorgiograesan.it)

<b>GIORGIO GRAESAN</b> and Friends	<b>TECHNICAL SHEET</b>  <b>PRIMUS AGGRAPPANTE</b>	Code	TDS1035_00
		Revision	00
		Date	22/08/2022

<b>TECHNICAL CHARACTERISTICS: APPLICATION</b>	
Dilution	Product is ready for use
Mixing	Always mix before use
Colouring	Not provided
Tools	Trowel KIT/I
Primer	Not provided
Conditions of application	From +10°C to +35°C with relative humidity < 85%
Number of coats	1 or 2 depending on the surface to be smoothed
Drying time	Each coat dries in 24 hours at 20°C
Curing time	24 hours at 20°C
Protecting	Not provided
Washability	Not provided

<b>TECHNICAL CHARACTERISTICS: COVERAGE</b>	
PRIMUS AGGRAPPANTE	1.7 m <sup>2</sup> /litre

<b>TECHNICAL CHARACTERISTICS: PRODUCT</b>	
Composition	Acrylic copolymer in aqueous emulsion, additives, mineral fillers
Specific weight	1.80 ± 0.10 kg/litre
pH	7.5 – 8.5
EU limit value (Directive 2004/42/EC) Cat. A/g:primer (water-borne): 30 g/l	Maximum VOC content 0.17 g/l
Condizioni di stoccaggio	Keep in tightly sealed container, even after use and after cleaning the sides and lid of the tin, in a cool, dry place at temperatures between +5°C and +30°C
Confezioni	2.5 – 5 litres

Giorgio Graesan & Friends guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge, however cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. We recommend always checking the actual suitability of the product for each specific case. This sheet nullifies and replaces any previous version.

For more information, call phone number **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.