

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDSTESSUTO_00
	SARTI IN PARETE	Revision	00
		Date	05/11/2024

1. DESCRIPTION

SARTI IN PARETE is a collection of **provocative non-woven** fabric designs coordinated with our paintings. From our exciting color ranges, four iconic designs are born that create situations and environments full of wonder and life for a total of 42 solutions. The fabric is perfectly **washable** and at the same time **breathable**. It can also be **painted over**, allowing for overlapping with our decorative paints that can be customised as desired based on taste and creativity.

The non-woven fabric rolls consist of three sheets, each 70 cm wide and 300 cm long. When placed side by side, they form a total design measuring 210 cm wide and 300 cm high..

The **shades** are coordinated with the colour ranges of our paints so that it is very easy to create the right combinations on the different walls.

2. USE

SARTI IN PARETE is suitable for decorating various types of **internal** wall surfaces.

The product is not suitable for non-absorbent, imperfect and damp surfaces.

3. SUBSTRATE PREPARATION

Correct preparation of the substrate is essential for a perfect finish. Proceed therefore with the elimination of any loose or flaking paint or plaster, taking care to wash or brush any presence of mold and dust.

All substrates must be dry, absorbent and free of paint and oil. Any cracks or holes in the wall must be filled with a light filler and in case of imperfections smooth with a normal plaster filler. It is always advisable to apply an acrylic fixative for consolidation and cleaning.

4. APPLICATION METHOD

This fabric is applied with our **COLLA PER TESSUTI**, previously spread on the wall with our PE10 brush, following the simple instructions given in the video tutorials linked to this QR-code:



5. TOOL CLEANING

Cleaning of the tools should be performed immediately after use with water.

6. PROTECTION AND CLEANING

The fabric and inks used (fixed with a special UV-curing process) are already highly washable. For added protection, 48 hours after applying the fabric, apply two coats of VETRO LUCIDO, VETRO OPACO or IPERVETRO, with a PE13 roller. You can also apply a first coat of IPERVETRO and a second coat of OPACO or VETRO LUCIDO. The protected wall thus becomes resistant to the most common substances, as indicated in the technical data sheets..

GIORGIO GRAESAN and Friends	TECHNICAL SHEET SARTI IN PARETE	Code	TDSTESSUTO_00
		Revision	00
		Date	05/11/2024

7. SAFETY INDICATIONS AND HAZARD IDENTIFICATION

The product does not require labelling according to current regulations. Use the product according to current health and safety regulations; after use, do not dispose of containers to the environment; let residue dry thoroughly and handle as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. Do not empty into drains, waterways or soil.

For more information, see safety data sheet available on: www.giorgiograesan.it

TECHNICAL SPECIFICATIONS: APPLICATION	
Weight	130 g/m ²
Roll width	70 cm
Roll length	960 cm
Color	42 designs with our standard range of colours
Tools	Application of COLLA PER TESSUTI: PE10 brush Wallpaper spatula and roller
Primer	Not provided
Application conditions	From +10°C to +30°C with relative humidity < 85%
Drying time	24 hours
Washability	Good washability. Full wash with LATTE DETERGENTE if protected with VETRO LUCIDO, VETRO OPACO or IPERVETRO
HACCP	Certification available for protections made with VETRO OPACO and IPERVETRO (downloadable from our website)

TECHNICAL SPECIFICATIONS: PRODUCT	
Composition	TNT (non-woven fabric)
Fire resistance	Bs1d0. Non-Fire Europe: Very limited contribution to widespread conflagration, combustible (EN13501-1). (Non-contractual; only the certificate confirms the fire safety standard).
Packaging	Single roll

Giorgio Graesan & Friends guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge, however cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. We recommend always checking the actual suitability of the product for each specific case. This sheet nullifies and replaces any previous version.

For more information, call phone number **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.